

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

Product Description:	<b>p-Xylene</b>
Cat No. :	<b>220210000; 220210010; 220210025</b>
Synonyms	1,4-Dimethylbenzene
Index No	601-022-00-9
CAS No	106-42-3
EC No	203-396-5
Molecular Formula	C8 H10

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use	Laboratory chemicals.
Uses advised against	No Information available

### 1.3. Details of the supplier of the safety data sheet

#### Company

**UK entity/business name**  
Fisher Scientific UK  
Bishop Meadow Road,  
Loughborough, Leicestershire LE11 5RG, United Kingdom

**EU entity/business name**  
Thermo Fisher Scientific  
Janssen Pharmaceuticaaan 3a, 2440 Geel, Belgium

E-mail address begel.sdsdesk@thermofisher.com

### 1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11  
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99  
**CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

#### CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

#### Physical hazards

Flammable liquids

Category 3 (H226)

#### Health hazards

# SAFETY DATA SHEET

p-Xylene

Revision Date 27-Sep-2023

Aspiration Toxicity	Category 1 (H304)
Acute dermal toxicity	Category 4 (H312)
Acute Inhalation Toxicity - Vapors	Category 4 (H332)
Skin Corrosion/Irritation	Category 2 (H315)
Serious Eye Damage/Eye Irritation	Category 2 (H319)
Specific target organ toxicity - (single exposure)	Category 3 (H335)

## Environmental hazards

Chronic aquatic toxicity	Category 3 (H412)
--------------------------	-------------------

Full text of Hazard Statements: see section 16

## 2.2. Label elements



Signal Word

Danger

## **Hazard Statements**

- H226 - Flammable liquid and vapor
- H304 - May be fatal if swallowed and enters airways
- H315 - Causes skin irritation
- H319 - Causes serious eye irritation
- H335 - May cause respiratory irritation
- H412 - Harmful to aquatic life with long lasting effects
- H312 + H332 - Harmful in contact with skin or if inhaled

## **Precautionary Statements**

- P280 - Wear protective gloves/protective clothing/eye protection/face protection
- P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

## 2.3. Other hazards

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB)

This product does not contain any known or suspected endocrine disruptors

## **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

### 3.1. Substances

Component	CAS No	EC No	Weight %	CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567
-----------	--------	-------	----------	---

# SAFETY DATA SHEET

p-Xylene

Revision Date 27-Sep-2023

p-Xylene	106-42-3	EEC No. 203-396-5	>95	Asp. Tox. 1 (H304) Acute Tox. 4 (H312) Skin Irrit. 2 (H315) Flam. Liq. 3 (H226) Acute Tox. 4 (H332) Eye Irrit. 2 (H319) STOT SE 3 (H335) Aquatic Chronic 3 (H412)
----------	----------	-------------------	-----	--

Full text of Hazard Statements: see section 16

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

<b>Eye Contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.
<b>Skin Contact</b>	Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.
<b>Ingestion</b>	Aspiration hazard. Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.
<b>Inhalation</b>	Remove to fresh air. If breathing is difficult, give oxygen. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required. Risk of serious damage to the lungs (by aspiration).
<b>Self-Protection of the First Aider</b>	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

### 4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. . Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

### 4.3. Indication of any immediate medical attention and special treatment needed

**Notes to Physician** Treat symptomatically.

## SECTION 5: FIREFIGHTING MEASURES

### 5.1. Extinguishing media

#### Suitable Extinguishing Media

CO<sub>2</sub>, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.

#### Extinguishing media which must not be used for safety reasons

Water may be ineffective.

### 5.2. Special hazards arising from the substance or mixture

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and

# SAFETY DATA SHEET

p-Xylene

Revision Date 27-Sep-2023

empty container away from heat and sources of ignition.

## **Hazardous Combustion Products**

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>), Hydrocarbons, Aldehydes.

### **5.3. Advice for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### **6.1. Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges. Avoid contact with skin, eyes or clothing.

### **6.2. Environmental precautions**

Avoid release to the environment. See Section 12 for additional Ecological Information. Do not flush into surface water or sanitary sewer system. Collect spillage.

### **6.3. Methods and material for containment and cleaning up**

Remove all sources of ignition. Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Use spark-proof tools and explosion-proof equipment.

### **6.4. Reference to other sections**

Refer to protective measures listed in Sections 8 and 13.

## **SECTION 7: HANDLING AND STORAGE**

### **7.1. Precautions for safe handling**

Use only under a chemical fume hood. Use spark-proof tools and explosion-proof equipment. Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Use only non-sparking tools.

### **Hygiene Measures**

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

### **7.2. Conditions for safe storage, including any incompatibilities**

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area.

**Technical Rules for Hazardous Substances (TRGS) 510**      Class 3  
**Storage Class (LGK) (Germany)**

### **7.3. Specific end use(s)**

Use in laboratories

# SAFETY DATA SHEET

p-Xylene

Revision Date 27-Sep-2023

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

#### Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

Component	The United Kingdom	European Union	Ireland
p-Xylene	STEL: 100 ppm 15 min STEL: 441 mg/m <sup>3</sup> 15 min TWA: 50 ppm 8 hr TWA: 220 mg/m <sup>3</sup> 8 hr Skin	TWA: 50 ppm (8h) TWA: 221 mg/m <sup>3</sup> (8h) STEL: 100 ppm (15min) STEL: 442 mg/m <sup>3</sup> (15min) Skin	TWA: 50 ppm 8 hr. TWA: 221 mg/m <sup>3</sup> 8 hr. STEL: 100 ppm 15 min STEL: 442 mg/m <sup>3</sup> 15 min Skin

#### Biological limit values

List source(s): **UK** - Biological Monitoring Guidance Values provided by the UK's Health and Safety Executive (HSE) Control of Substances Hazardous to Health Regulations (COSHH) 2002 (as amended) and EH40/2005.

Component	United Kingdom	European Union
p-Xylene	Methyl hippuric acid: 650 mmol/mol creatinine urine post shift	

#### Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
p-Xylene 106-42-3 (>95)				DNEL = 212mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
p-Xylene 106-42-3 (>95)	DNEL = 442mg/m <sup>3</sup>	DNEL = 442mg/m <sup>3</sup>	DNEL = 221mg/m <sup>3</sup>	DNEL = 221mg/m <sup>3</sup>

#### Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
p-Xylene 106-42-3 (>95)	PNEC = 0.044mg/L PNEC = 0.327mg/L	PNEC = 2.52mg/kg sediment dw PNEC = 12.46mg/kg sediment dw	PNEC = 0.01mg/L PNEC = 0.327mg/L	PNEC = 1.6mg/L PNEC = 6.58mg/L	PNEC = 0.852mg/kg soil dw PNEC = 2.31mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water intermittent	Food chain	Air
p-Xylene 106-42-3 (>95)	PNEC = 0.0044mg/L PNEC = 0.327mg/L	PNEC = 0.252mg/kg sediment dw PNEC = 12.46mg/kg sediment dw	PNEC = 0.001mg/L		

# SAFETY DATA SHEET

p-Xylene

Revision Date 27-Sep-2023

## 8.2. Exposure controls

### Engineering Measures

Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

### Personal protective equipment

**Eye Protection** Goggles (European standard - EN 166)

**Hand Protection** Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Nitrile rubber	See manufacturers recommendations	-	EN 374	(minimum requirement)
Neoprene				
Natural rubber				
PVC				

**Skin and body protection** Wear appropriate protective gloves and clothing to prevent skin exposure.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatibility, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

**Respiratory Protection** When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

**Large scale/emergency use** Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced  
**Recommended Filter type:** Organic gases and vapours filter Type A Brown conforming to EN14387

**Small scale/Laboratory use** Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.  
**Recommended half mask:-** Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141  
When RPE is used a face piece Fit Test should be conducted

**Environmental exposure controls** Prevent product from entering drains. Do not allow material to contaminate ground water system.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

**Physical State** Liquid

**Appearance** Colorless

**Odor** aromatic

**Odor Threshold** No data available

**Melting Point/Range** 13 °C / 55.4 °F

**Softening Point** No data available

# SAFETY DATA SHEET

p-Xylene

Revision Date 27-Sep-2023

<b>Boiling Point/Range</b>	138 °C / 280.4 °F	
<b>Flammability (liquid)</b>	Flammable	On basis of test data
<b>Flammability (solid,gas)</b>	Not applicable	Liquid
<b>Explosion Limits</b>	<b>Lower</b> 1.1 Vol% <b>Upper</b> 7 Vol%	
<b>Flash Point</b>	25 °C / 77 °F	<b>Method</b> - No information available
<b>Autoignition Temperature</b>	465 °C / 869 °F	
<b>Decomposition Temperature</b>	No data available	
<b>pH</b>	Not applicable	
<b>Viscosity</b>	0.648 mPa.s (20°C)	
<b>Water Solubility</b>	0.2 g/L (20°C)	practically insoluble
<b>Solubility in other solvents</b>	No information available	
<b>Partition Coefficient (n-octanol/water)</b>		
<b>Component</b>	<b>log Pow</b>	
p-Xylene	3.2	
<b>Vapor Pressure</b>	8 mbar @ 20 °C	
<b>Density / Specific Gravity</b>	0.866	
<b>Bulk Density</b>	Not applicable	Liquid
<b>Vapor Density</b>	3.7 (Air = 1.0)	(Air = 1.0)
<b>Particle characteristics</b>	(liquid) Not applicable	

## 9.2. Other information

<b>Molecular Formula</b>	C8 H10
<b>Molecular Weight</b>	106.17
<b>Explosive Properties</b>	explosive air/vapour mixtures possible

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

None known, based on information available

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

<b>Hazardous Polymerization</b>	Hazardous polymerization does not occur.
<b>Hazardous Reactions</b>	None under normal processing.

### 10.4. Conditions to avoid

Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition.

### 10.5. Incompatible materials

Strong oxidizing agents. Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Hydrocarbons. Aldehydes.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Product Information

# SAFETY DATA SHEET

p-Xylene

Revision Date 27-Sep-2023

**(a) acute toxicity;**

**Oral** Based on available data, the classification criteria are not met  
**Dermal** Category 4  
**Inhalation** Category 4

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
p-Xylene	LD50 = 4029 mg/kg ( Rat )	LD50 = 12126 mg/kg ( Rabbit )	LC50 = 4740 ppm ( Rat ) 4 h

**(b) skin corrosion/irritation;** Category 2

**(c) serious eye damage/irritation;** Category 2

**(d) respiratory or skin sensitization;**

**Respiratory** No data available  
**Skin** No data available

**(e) germ cell mutagenicity;** No data available

**(f) carcinogenicity;** No data available

There are no known carcinogenic chemicals in this product

**(g) reproductive toxicity;**

**Reproductive Effects** No data available  
**Developmental Effects** Experiments have shown reproductive toxicity effects on laboratory animals.  
**Teratogenicity** Developmental effects have occurred in experimental animals.  
Teratogenic effects have occurred in experimental animals.

**(h) STOT-single exposure;** Category 3

**Results / Target organs** Respiratory system.

**(i) STOT-repeated exposure;** No data available

**Target Organs** No information available.

**(j) aspiration hazard;** Category 1

**Other Adverse Effects** See actual entry in RTECS for complete information

**Symptoms / effects,both acute and delayed** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

**11.2. Information on other hazards**

**Endocrine Disrupting Properties** Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

## SECTION 12: ECOLOGICAL INFORMATION

**12.1. Toxicity**

**Ecotoxicity effects**

Do not empty into drains. The product contains following substances which are hazardous for the environment. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Contains a substance which is: Toxic to aquatic organisms.



# SAFETY DATA SHEET

p-Xylene

Revision Date 27-Sep-2023

Component	Freshwater Fish	Water Flea	Freshwater Algae
p-Xylene	LC50: = 8.8 mg/L, 96h semi-static (Poecilia reticulata) LC50: = 2.6 mg/L, 96h static (Oncorhynchus mykiss) LC50: = 2.6 mg/L, 96h (Oncorhynchus mykiss) LC50: 7.2 - 9.9 mg/L, 96h static (Pimephales promelas)	EC50: 3.55 - 6.31 mg/L, 48h Static (Daphnia magna)	EC50: = 3.2 mg/L, 72h static (Pseudokirchneriella subcapitata)

Component	Microtox	M-Factor
p-Xylene	EC50 = 5.7 mg/L 30 min	

**12.2. Persistence and degradability** Expected to be biodegradable  
**Persistence** Insoluble in water, Persistence is unlikely, based on information available.  
**Degradation in sewage treatment plant** Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

**12.3. Bioaccumulative potential** May have some potential to bioaccumulate

Component	log Pow	Bioconcentration factor (BCF)
p-Xylene	3.2	2.2 dimensionless

**12.4. Mobility in soil** Spillage unlikely to penetrate soil The product is insoluble and floats on water The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces . Is not likely mobile in the environment due its low water solubility. Will likely be mobile in the environment due to its volatility.

**12.5. Results of PBT and vPvB assessment** Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB).

**12.6. Endocrine disrupting properties**  
**Endocrine Disruptor Information** This product does not contain any known or suspected endocrine disruptors

**12.7. Other adverse effects**  
**Persistent Organic Pollutant** This product does not contain any known or suspected substance  
**Ozone Depletion Potential** This product does not contain any known or suspected substance

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

**Waste from Residues/Unused Products** Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

**Contaminated Packaging** Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

**European Waste Catalogue (EWC)** According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

**Other Information** Do not flush to sewer. Waste codes should be assigned by the user based on the

# SAFETY DATA SHEET

p-Xylene

Revision Date 27-Sep-2023

application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not let this chemical enter the environment. Do not empty into drains.

## SECTION 14: TRANSPORT INFORMATION

### IMDG/IMO

**14.1. UN number** UN1307  
**14.2. UN proper shipping name** XYLENES  
**14.3. Transport hazard class(es)** 3  
**14.4. Packing group** III

### ADR

**14.1. UN number** UN1307  
**14.2. UN proper shipping name** XYLENES  
**14.3. Transport hazard class(es)** 3  
**14.4. Packing group** III

### IATA

**14.1. UN number** UN1307  
**14.2. UN proper shipping name** XYLENES  
**14.3. Transport hazard class(es)** 3  
**14.4. Packing group** III

**14.5. Environmental hazards** No hazards identified  
**14.6. Special precautions for user** No special precautions required.  
**14.7. Maritime transport in bulk according to IMO instruments** Not applicable, packaged goods

## SECTION 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
p-Xylene	106-42-3	203-396-5	-	-	X	X	KE-35430	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
p-Xylene	106-42-3	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

# SAFETY DATA SHEET

p-Xylene

Revision Date 27-Sep-2023

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
p-Xylene	106-42-3	-	Use restricted. See item 75. (see link for restriction details)	-

**REACH links**

<https://echa.europa.eu/substances-restricted-under-reach>

**Seveso III Directive (2012/18/EC)**

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
p-Xylene	106-42-3	Not applicable	Not applicable

**Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals**

Not applicable

**Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?**

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

**National Regulations**

**UK** - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

**WGK Classification**

See table for values

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
p-Xylene	WGK2	

Component	France - INRS (Tables of occupational diseases)
p-Xylene	Tableaux des maladies professionnelles (TMP) - RG 4bis, RG 84

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
p-Xylene 106-42-3 (>95)	Prohibited and Restricted Substances	Group I	

**15.2. Chemical safety assessment**

A Chemical Safety Assessment/Report (CSA/CSR) has not been conducted

# SAFETY DATA SHEET

p-Xylene

Revision Date 27-Sep-2023

## SECTION 16: OTHER INFORMATION

### Full text of H-Statements referred to under sections 2 and 3

H226 - Flammable liquid and vapor  
H304 - May be fatal if swallowed and enters airways  
H312 - Harmful in contact with skin  
H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H332 - Harmful if inhaled  
H335 - May cause respiratory irritation  
H412 - Harmful to aquatic life with long lasting effects

### Legend

**CAS** - Chemical Abstracts Service

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**IECSC** - Chinese Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List

**ENCS** - Japanese Existing and New Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**NZIoC** - New Zealand Inventory of Chemicals

**WEL** - Workplace Exposure Limit

**ACGIH** - American Conference of Governmental Industrial Hygienists

**DNEL** - Derived No Effect Level

**RPE** - Respiratory Protective Equipment

**LC50** - Lethal Concentration 50%

**NOEC** - No Observed Effect Concentration

**PBT** - Persistent, Bioaccumulative, Toxic

**TWA** - Time Weighted Average

**IARC** - International Agency for Research on Cancer Predicted No Effect Concentration (PNEC)

**LD50** - Lethal Dose 50%

**EC50** - Effective Concentration 50%

**POW** - Partition coefficient Octanol:Water

**vPvB** - very Persistent, very Bioaccumulative

**ADR** - European Agreement Concerning the International Carriage of Dangerous Goods by Road

**IMO/IMDG** - International Maritime Organization/International Maritime Dangerous Goods Code

**OECD** - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

**Key literature references and sources for data**

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

**ICAO/IATA** - International Civil Aviation Organization/International Air Transport Association

**MARPOL** - International Convention for the Prevention of Pollution from Ships

**ATE** - Acute Toxicity Estimate

**VOC** - (Volatile Organic Compound)

### Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

**Creation Date** 24-Mar-2014

**Revision Date** 27-Sep-2023

**Revision Summary** Not applicable.

**This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.**

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information

# SAFETY DATA SHEET

p-Xylene

Revision Date 27-Sep-2023

---

relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**