

according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended

Creation Date 10-Dec-2009 Revision Date 11-Oct-2023 Revision Number 9

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: Osmium tetroxide, 2.5 wt% solution in t-butanol, stabilized

Cat No. : 429080000; 429081000

Molecular Formula O4 Os

Unique Formula Identifier (UFI) UU4G-2TT2-AW09-8W4Y

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.

Sector of use SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

Product category PC21 - Laboratory chemicals

Process categories PROC15 - Use as a laboratory reagent

Environmental release category ERC6a - Industrial use resulting in manufacture of another substance (use of intermediates)

Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

UK entity/business name

Fisher Scientific UK Bishop Meadow Road,

Loughborough, Leicestershire LE11 5RG, United Kingdom

EU entity/business name Thermo Fisher Scientific

Janssen Pharmaceuticalaan 3a, 2440 Geel, Belgium

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

Poison Centre - Emergency information services

Ireland: National Poisons Information Centre (NPIC) -

01 809 2166 (8am-10pm, 7 days a week)

Malta: +356 2395 2000 Cyprus: +357 2240 5611

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Osmium tetroxide, 2.5 wt% solution in t-butanol, stabilized

Revision Date 11-Oct-2023

Physical hazards

Flammable liquids Category 2 (H225)

Health hazards

Acute oral toxicity

Acute dermal toxicity

Acute Inhalation Toxicity - Vapors

Skin Corrosion/Irritation

Serious Eye Damage/Eye Irritation

Respiratory Sensitization

Specific target organ toxicity - (single exposure)

Category 4 (H302)

Category 2 (H310)

Category 3 (H331)

Category 2 (H315)

Category 2 (H319)

Category 1 (H334)

Category 3 (H335) (H336)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

- H225 Highly flammable liquid and vapor
- H302 Harmful if swallowed
- H310 Fatal in contact with skin
- H331 Toxic if inhaled
- H315 Causes skin irritation
- H319 Causes serious eye irritation
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled
- H335 May cause respiratory irritation
- H336 May cause drowsiness or dizziness

Precautionary Statements

- P301 + P330 + P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting
- P264 Wash face, hands and any exposed skin thoroughly after handling
- P310 Immediately call a POISON CENTER or doctor/physician
- P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing
- P280 Wear protective gloves/protective clothing/eye protection/face protection
- P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

2.3. Other hazards

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB)

Revision Date 11-Oct-2023

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567
Osmium tetroxide	20816-12-0	EEC No. 244-058-7	2.5	Acute Tox. 2 (H300) Acute Tox. 1 (H310) Acute Tox. 2 (H330) Skin Corr. 1B (H314) Eye Dam. 1 (H318) Resp. Sens. 1 (H334)
tert-Butyl alcohol	75-65-0	EEC No. 200-889-7	97.5	Flam. Liq. 2 (H225) Eye Irrit. 2 (H319) Acute Tox. 4 (H332) STOT SE 3 (H335) STOT SE 3 (H336)

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice Show this safety data sheet to the doctor in attendance. Immediate medical attention is

required.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In

the case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Immediate medical

attention is required.

Ingestion Do NOT induce vomiting. Call a physician or poison control center immediately.

InhalationIf not breathing, give artificial respiration. Remove to fresh air. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a

pocket mask equipped with a one-way valve or other proper respiratory medical device.

Immediate medical attention is required.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

May cause allergy or asthma symptoms or breathing difficulties if inhaled. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of

Osmium tetroxide, 2.5 wt% solution in t-butanol, stabilized

Revision Date 11-Oct-2023

perforation

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

No information available.

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon dioxide (CO₂), Carbon monoxide (CO).

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Remove all sources of ignition. Take precautionary measures against static discharges.

6.2. Environmental precautions

Should not be released into the environment.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from

Osmium tetroxide, 2.5 wt% solution in t-butanol, stabilized

Revision Date 11-Oct-2023

open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Corrosives area. To maintain product quality: Keep refrigerated. Flammables area.

Class 3

Technical Rules for Hazardous Substances (TRGS) 510 Storage Class (LGK) (Germany)

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

Component	The United Kingdom	European Union	Ireland
Osmium tetroxide	STEL: 0.0006 ppm 15 min		TWA: 0.002 mg/m ³ 8 hr. Os
	STEL: 0.006 mg/m ³ 15 min		TWA: 0.0002 ppm 8 hr. Os
	TWA: 0.0002 ppm 8 hr		STEL: 0.006 mg/m ³ 15 min
	TWA: 0.002 mg/m ³ 8 hr		STEL: 0.0006 ppm 15 min
tert-Butyl alcohol	STEL: 150 ppm 15 min		TWA: 100 ppm 8 hr.
	STEL: 462 mg/m ³ 15 min		TWA: 300 mg/m ³ 8 hr.
	TWA: 100 ppm 8 hr		STEL: 300 ppm 15 min
	TWA: 308 mg/m ³ 8 hr		STEL 900 mg/m ³ 15 min

Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
tert-Butyl alcohol				DNEL = 5.5mg/kg
75-65-0 (97.5)				bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
tert-Butyl alcohol 75-65-0 (97.5)		DNEL = 214mg/m ³		$DNEL = 2.7 mg/m^3$

Osmium tetroxide, 2.5 wt% solution in t-butanol, stabilized

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water	Water Intermittent	Microorganisms in	Soil (Agriculture)
		sediment		sewage treatment	
tert-Butyl alcohol	PNEC = 2mg/L	PNEC = 8.04 mg/kg	PNEC = 9.33mg/L	PNEC = 690mg/L	PNEC = 1mg/kg soil
75-65-0 (97.5)		sediment dw			dw

Component	Marine water	Marine water sediment	Marine water intermittent	Food chain	Air
tert-Butyl alcohol	PNEC = 0.2mg/L	PNEC =		PNEC = 88700g/kg	
75-65-0 (97.5)		0.804mg/kg sediment dw		food	

8.2. Exposure controls

Engineering Measures

Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation, especially in confined areas. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to

control hazardous materials at source

Personal protective equipment Eve Protection

Goggles (European standard - EN 166)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Natural rubber	See manufacturers	-	EN 374	(minimum requirement)
Nitrile rubber	recommendations			
Neoprene				
PVC				

Skin and body protection Long sleeved clothing.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits

are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: Organic gases and vapours filter Type A Brown conforming to

EN14387

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure

limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN

141

When RPE is used a face piece Fit Test should be conducted

Revision Date 11-Oct-2023

Osmium tetroxide, 2.5 wt% solution in t-butanol, stabilized

Revision Date 11-Oct-2023

Environmental exposure controls

Prevent product from entering drains. Do not allow material to contaminate ground water system.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State Liquid

Appearance

Odor
Odor No information available
No data available
Melting Point/Range
No data available
No data available
No data available
No information available
No information available

Flammability (liquid) Highly flammable On basis of test data

Flammability (solid,gas) Not applicable Liquid

Explosion Limits No data available

Flash Point 4 °C / 39.2 °F Method - CC (closed cup)

Autoignition Temperature
Decomposition Temperature
pH
Viscosity
Water Solubility
Solubility in other solvents
No data available
No information available
No information available
No information available

Partition Coefficient (n-octanol/water)

Componentlog PowOsmium tetroxide0.9tert-Butyl alcohol0.317

Vapor Pressure 466 hPa @ 55°C

Density / Specific Gravity 0.811

Bulk DensityNot applicableLiquidVapor DensityNo data available(Air = 1.0)

Particle characteristics (liquid) Not applicable

9.2. Other information

Molecular FormulaO4 OsMolecular Weight254.2

Explosive Properties Vapors may form explosive mixtures with air

Evaporation Rate negligible

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

10.4. Conditions to avoid

Excess heat. Incompatible products. Keep away from open flames, hot surfaces and

.____

Osmium tetroxide, 2.5 wt% solution in t-butanol, stabilized

sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Carbon dioxide (CO₂). Carbon monoxide (CO).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral Category 4
Dermal Category 2
Inhalation Category 3

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Osmium tetroxide	15 mg/kg (Rat)	-	LC50 = 40 ppm (Rat) 4 h
tert-Butyl alcohol	>3100 mg/kg (Rat)	>2000 mg/kg (Rabbit)	>31 mg/L/4h (Rat)

(b) skin corrosion/irritation; Category 2

(c) serious eye damage/irritation; Category 2

(d) respiratory or skin sensitization;

Respiratory Category 1

Skin Based on available data, the classification criteria are not met

Component	Test method	Test species	Study result
tert-Butyl alcohol	OECD Test Guideline 406	guinea pig	non-sensitising
75-65-0 (97.5)	Skin sensitization		_

No information available

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

Component	Test method	Test species	Study result
tert-Butyl alcohol	AMES test	in vitro	negative
75-65-0 (97.5)			-

(f) carcinogenicity; Based on available data, the classification criteria are not met

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; Based on available data, the classification criteria are not met

(h) STOT-single exposure; Category 3

Results / Target organs Respiratory system, Central nervous system (CNS).

ACR42908

Revision Date 11-Oct-2023

Osmium tetroxide, 2.5 wt% solution in t-butanol, stabilized

(i) STOT-repeated exposure; Based on available data, the classification criteria are not met

Target Organs None known.

(j) aspiration hazard; Based on available data, the classification criteria are not met

delayed

Symptoms / effects, both acute and Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation.

Revision Date 11-Oct-2023

11.2. Information on other hazards

Endocrine Disrupting Properties

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects

Do not empty into drains. .

Component	Freshwater Fish	Water Flea	Freshwater Algae
tert-Butyl alcohol	LC50 >961 mg/L/96h (Pimephales promelas)	EC50 933 mg/L 48 h	EC50 1000 mg/L 72 h

Component	Microtox	M-Factor
tert-Butyl alcohol	EC50 > 10000 mg/L 17 h	

12.2. Persistence and degradability Not applicable for mixtures

Persistence

Persistence is unlikely.

12.3. Bioaccumulative potential Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)		
Osmium tetroxide	0.9	No data available		
tert-Butvl alcohol	0.317	1.09 dimensionless		

12.4. Mobility in soil No information available

12.5. Results of PBT and vPvB

assessment

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB).

12.6. Endocrine disrupting

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant

This product does not contain any known or suspected substance

Osmium tetroxide, 2.5 wt% solution in t-butanol, stabilized

Revision Date 11-Oct-2023

This product does not contain any known or suspected substance **Ozone Depletion Potential**

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused

Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and

empty container away from heat and sources of ignition.

European Waste Catalogue (EWC)

According to the European Waste Catalog, Waste Codes are not product specific, but

application specific.

Other Information

Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations.

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number UN1992

14.2. UN proper shipping name Flammable liquid, toxic, n.o.s. **Technical Shipping Name** tert-Butyl alcohol, Osmium tetroxide

14.3. Transport hazard class(es) **Subsidiary Hazard Class** 6.1 14.4. Packing group П

ADR

14.1. UN number UN1992

14.2. UN proper shipping name Flammable liquid, toxic, n.o.s. **Technical Shipping Name** tert-Butyl alcohol, Osmium tetroxide

14.3. Transport hazard class(es) 3 **Subsidiary Hazard Class** 6.1 14.4. Packing group П

IATA

UN1992 14.1. UN number

14.2. UN proper shipping name Flammable liquid, toxic, n.o.s. **Technical Shipping Name** tert-Butyl alcohol, Osmium tetroxide

14.3. Transport hazard class(es) 3 **Subsidiary Hazard Class** 6.1 14.4. Packing group Π

No hazards identified 14.5. Environmental hazards

14.6. Special precautions for user No special precautions required.

Not applicable, packaged goods 14.7. Maritime transport in bulk according to IMO instruments

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Osmium tetroxide	20816-12-0	244-058-7	-	-	Х	X	KE-27435	-	-
tert-Butyl alcohol	75-65-0	200-889-7	-	-	Х	X	KE-24895	X	Х

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Osmium tetroxide	20816-12-0	X	ACTIVE	X	Ī	X	X	Х
tert-Butyl alcohol	75-65-0	Х	ACTIVE	X	-	X	Х	Х

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Osmium tetroxide	20816-12-0	-	Use restricted. See item 75. (see link for restriction details)	-
tert-Butyl alcohol	75-65-0	-	Use restricted. See item 75. (see link for restriction details)	-

REACH links

https://echa.europa.eu/substances-restricted-under-reach

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Osmium tetroxide	20816-12-0	Not applicable	Not applicable
tert-Butyl alcohol	75-65-0	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Osmium tetroxide, 2.5 wt% solution in t-butanol, stabilized

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

Water endangering class = 1 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
tert-Butyl alcohol	WGK1	

Component	France - INRS (Tables of occupational diseases)
tert-Butyl alcohol	Tableaux des maladies professionnelles (TMP) - RG 84

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H302 - Harmful if swallowed

H310 - Fatal in contact with skin

H331 - Toxic if inhaled

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled

H335 - May cause respiratory irritation

H336 - May cause drowsiness or dizziness

H225 - Highly flammable liquid and vapor

H300 - Fatal if swallowed

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

H330 - Fatal if inhaled

H332 - Harmful if inhaled

Legend

CAS - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

Revision Date 11-Oct-2023

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

Substances List **ENCS** - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50% POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

Osmium tetroxide, 2.5 wt% solution in t-butanol, stabilized

Revision Date 11-Oct-2023

ADR - European Agreement Concerning the International Carriage of

Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime

Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air

Transport Association

MARPOL - International Convention for the Prevention of Pollution from

Ships

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards

Health Hazards

Environmental hazards

On basis of test data
Calculation method
Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Creation Date 10-Dec-2009
Revision Date 11-Oct-2023
Revision Summary Not applicable.

This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet