

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: Nickel on silica-alumina, catalyst
Cat No. : 31276
Molecular Formula 66+5% Ni

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company Avocado Research Chemicals Ltd.
(Part of Thermo Fisher Scientific)
Shore Road, Heysham
Lancashire, LA3 2XY,
United Kingdom
Office Tel: +44 (0) 1524 850506
Office Fax: +44 (0) 1524 850608

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

Poison Centre - Emergency information services **Ireland** : National Poisons Information Centre (NPIC) -
01 809 2166 (8am-10pm, 7 days a week)
Malta : +356 2395 2000
Cyprus : +357 2240 5611

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

GHS Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Physical hazards

Flammable solids

Category 2 (H228)

Health hazards

SAFETY DATA SHEET

Nickel on silica-alumina, catalyst

Revision Date 30-Nov-2024

| | |
|--|---------------------|
| Skin Sensitization | Category 1 (H317) |
| Carcinogenicity | Category 1A (H350i) |
| Specific target organ toxicity - (repeated exposure) | Category 1 (H372) |
| <u>Environmental hazards</u> | |
| Chronic aquatic toxicity | Category 4 (H413) |

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H228 - Flammable solid

H317 - May cause an allergic skin reaction

H350i - May cause cancer by inhalation

H372 - Causes damage to organs through prolonged or repeated exposure

H413 - May cause long lasting harmful effects to aquatic life

Precautionary Statements

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water

P201 - Obtain special instructions before use

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P308 + P313 - IF exposed or concerned: Get medical advice/attention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Additional EU labelling

Restricted to professional users

2.3. Other hazards

Toxicity to Soil Dwelling Organisms

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

| Component | CAS No | EC No | Weight % | GHS Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567 |
|-----------|-----------|-----------|----------|---|
| Nickel | 7440-02-0 | 231-111-4 | 50.0 | Flam. Sol. 2 (H228) Skin Sens. 1 (H317) Carc. 2 (H351) |

SAFETY DATA SHEET

Nickel on silica-alumina, catalyst

Revision Date 30-Nov-2024

| | | | | |
|-------------------|-----------|-------------------|------|---|
| | | | | STOT RE 1 (H372) Aquatic Chronic 3 (H412) |
| Nickel oxide | 1313-99-1 | EEC No. 215-215-7 | 25.0 | Skin Sens. 1 (H317) Carc. 1A (H350i) STOT RE 1 (H372) Aquatic Chronic 4 (H413) |
| Aluminum oxide | 1344-28-1 | 215-691-6 | 13 | - |
| Silica, amorphous | 7631-86-9 | EEC No. 231-545-4 | 12.0 | - |

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

| | |
|---|--|
| General Advice | If symptoms persist, call a physician. |
| Eye Contact | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention. |
| Skin Contact | Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician. |
| Ingestion | Clean mouth with water and drink afterwards plenty of water. Get medical attention if symptoms occur. |
| Inhalation | Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur. |
| Self-Protection of the First Aider | Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. |

4.2. Most important symptoms and effects, both acute and delayed

May cause allergic skin reaction. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

approved class D extinguishers. Do not use water or foam.

Extinguishing media which must not be used for safety reasons

No information available.

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors.

SAFETY DATA SHEET

Nickel on silica-alumina, catalyst

Revision Date 30-Nov-2024

Hazardous Combustion Products

Silicon dioxide, Nickel oxides, Fumes of aluminum or aluminum oxide.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Avoid dust formation.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system. Should not be released into the environment. Do not allow material to contaminate ground water system.

6.3. Methods and material for containment and cleaning up

Sweep up and shovel into suitable containers for disposal. Keep in suitable, closed containers for disposal.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Avoid dust formation.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Technical Rules for Hazardous Substances (TRGS) 510 Class 4.1B
Storage Class (LGK) (Germany)

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

ALFAA31276

SAFETY DATA SHEET

Nickel on silica-alumina, catalyst

Revision Date 30-Nov-2024

Exposure limits

List source(s): **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

| Component | The United Kingdom | European Union | Ireland |
|-------------------|---|----------------|--|
| Nickel | STEL: 1.5 mg/m ³ 15 min TWA: 0.5 mg/m ³ 8 hr Skin | | TWA: 0.5 mg/m ³ 8 hr. STEL: 1.5 mg/m ³ 15 min |
| Nickel oxide | STEL: 1.5 mg/m ³ 15 min TWA: 0.5 mg/m ³ 8 hr Skin | | |
| Aluminum oxide | STEL: 30 mg/m ³ 15 min STEL: 12 mg/m ³ 15 min TWA: 10 mg/m ³ 8 hr TWA: 4 mg/m ³ 8 hr | | |
| Silica, amorphous | STEL: 18 mg/m ³ 15 min STEL: 7.2 mg/m ³ 15 min TWA: 6 mg/m ³ 8 hr TWA: 2.4 mg/m ³ 8 hr | | TWA: 6 mg/m ³ 8 hr. total inhalable dust TWA: 2.4 mg/m ³ 8 hr. respirable dust STEL: 18 mg/m ³ 15 min STEL: 7.2 mg/m ³ 15 min |

Biological limit values

List source(s):

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

| Component | Acute effects local (Dermal) | Acute effects systemic (Dermal) | Chronic effects local (Dermal) | Chronic effects systemic (Dermal) |
|------------------------------------|------------------------------|---------------------------------|--------------------------------|-----------------------------------|
| Nickel 7440-02-0 (50.0) | | | DNEL = 0.035mg/cm ² | |
| Nickel oxide 1313-99-1 (25.0) | | | DNEL = 0.012mg/cm ² | |

| Component | Acute effects local (Inhalation) | Acute effects systemic (Inhalation) | Chronic effects local (Inhalation) | Chronic effects systemic (Inhalation) |
|------------------------------------|----------------------------------|-------------------------------------|------------------------------------|---------------------------------------|
| Nickel 7440-02-0 (50.0) | DNEL = 11.9mg/m ³ | | DNEL = 0.05mg/m ³ | DNEL = 0.05mg/m ³ |
| Nickel oxide 1313-99-1 (25.0) | DNEL = 18.9mg/m ³ | | DNEL = 0.05mg/m ³ | DNEL = 0.05mg/m ³ |

Predicted No Effect Concentration (PNEC)

See values below.

| Component | Fresh water | Fresh water sediment | Water Intermittent | Microorganisms in sewage treatment | Soil (Agriculture) |
|------------------------------------|-------------------|-----------------------------|--------------------|------------------------------------|--------------------------|
| Nickel 7440-02-0 (50.0) | PNEC = 7.1µg/L | PNEC = 109mg/kg sediment dw | | PNEC = 0.33mg/L | PNEC = 29.9mg/kg soil dw |
| Nickel oxide 1313-99-1 (25.0) | PNEC = 7.1µg/L | PNEC = 109mg/kg sediment dw | | PNEC = 0.33mg/L | PNEC = 29.9mg/kg soil dw |
| Aluminum oxide 1344-28-1 (13) | PNEC = 0.3136µg/L | | PNEC = 3.136µg/L | PNEC = 20mg/L | |

| Component | Marine water | Marine water sediment | Marine water intermittent | Food chain | Air |
|-----------|----------------|-----------------------|---------------------------|------------------|-----|
| Nickel | PNEC = 8.6µg/L | PNEC = 109mg/kg | | PNEC = 0.12mg/kg | |

SAFETY DATA SHEET

Nickel on silica-alumina, catalyst

Revision Date 30-Nov-2024

| | | | |
|------------------------------------|----------------|--------------------------------|--------------------------|
| 7440-02-0 (50.0) | | sediment dw | food |
| Nickel oxide 1313-99-1 (25.0) | PNEC = 8.6µg/L | PNEC = 109mg/kg sediment dw | PNEC = 0.12mg/kg food |

8.2. Exposure controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Wear safety glasses with side shields (or goggles) (European standard - EN 166)

Hand Protection

Protective gloves

| Glove material | Breakthrough time | Glove thickness | EU standard | Glove comments |
|----------------|-------------------|-----------------|-------------|-----------------------|
| Natural rubber | See manufacturers | - | EN 374 | (minimum requirement) |
| Nitrile rubber | recommendations | | | |
| Neoprene | | | | |
| PVC | | | | |

Skin and body protection

Long sleeved clothing.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatibility, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: Particulates filter conforming to EN 143

Small scale/Laboratory use

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Particle filtering: EN149:2001

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls

Prevent product from entering drains. Do not allow material to contaminate ground water system. Local authorities should be advised if significant spillages cannot be contained.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

| | |
|----------------------------|-------------------|
| Physical State | Solid |
| Appearance | Grey |
| Odor | Odorless |
| Odor Threshold | No data available |
| Melting Point/Range | No data available |
| Softening Point | No data available |

SAFETY DATA SHEET

Nickel on silica-alumina, catalyst

Revision Date 30-Nov-2024

| | | |
|--|--------------------------|--|
| Boiling Point/Range | No information available | |
| Flammability (liquid) | Not applicable | Solid |
| Flammability (solid,gas) | No information available | |
| Explosion Limits | No data available | |
| Flash Point | No information available | Method - No information available |
| Autoignition Temperature | No data available | |
| Decomposition Temperature | No data available | |
| pH | No information available | |
| Viscosity | Not applicable | Solid |
| Water Solubility | Insoluble in water | |
| Solubility in other solvents | No information available | |
| Partition Coefficient (n-octanol/water) | | |
| Vapor Pressure | No data available | |
| Density / Specific Gravity | No data available | |
| Bulk Density | No data available | |
| Vapor Density | Not applicable | Solid |
| Particle characteristics | No data available | |

9.2. Other information

| | |
|--------------------------|---|
| Molecular Formula | 66+5% Ni |
| Flammable solids | Burning rate or burning time = > 2.2 mm/s or < 45 secs Wetted zone passed - No |
| Evaporation Rate | Not applicable - Solid |

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity None known, based on information available

10.2. Chemical stability Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization No information available.
Hazardous Reactions None under normal processing.

10.4. Conditions to avoid Incompatible products. Excess heat.

10.5. Incompatible materials Oxidizing agent.

10.6. Hazardous decomposition products Silicon dioxide. Nickel oxides. Fumes of aluminum or aluminum oxide.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;
Oral Based on available data, the classification criteria are not met

SAFETY DATA SHEET

Nickel on silica-alumina, catalyst

Revision Date 30-Nov-2024

Dermal
Inhalation

Based on available data, the classification criteria are not met
Based on available data, the classification criteria are not met

Toxicology data for the components

| Component | LD50 Oral | LD50 Dermal | LC50 Inhalation |
|-------------------|--|------------------------|--|
| Nickel | LD50 > 9000 mg/kg (Rat) | - | LC50 > 10.2 mg/L (Rat) 1 h |
| Nickel oxide | LD50 > 5000 mg/kg (Rat) | - | LC50 > 5.08 mg/L (Rat) 4 h |
| Aluminum oxide | > 5000 mg/kg (Rat) (OECD Guideline 401) | - | > 2.3 mg/l 4 h (OECD Guideline 403) |
| Silica, amorphous | >5000 mg/kg (Rat) | >2000 mg/kg (Rabbit) | - |

(b) skin corrosion/irritation; No data available

(c) serious eye damage/irritation; No data available

(d) respiratory or skin sensitization;

Respiratory No data available
Skin Category 1

May cause sensitization by skin contact

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; Category 1A

The table below indicates whether each agency has listed any ingredient as a carcinogen

| Component | EU | UK | Germany | IARC |
|----------------|--------------|----|---------------------|----------|
| Nickel | | | Cat. 1 | Group 2B |
| Nickel oxide | Carc Cat. 1A | | Cat. 1 | Group 1 |
| Aluminum oxide | | | Cat. 2 (Fibre dust) | |

(g) reproductive toxicity; No data available

(h) STOT-single exposure; No data available

(i) STOT-repeated exposure; Category 1

Route of exposure Inhalation
Target Organs Lungs.

(j) aspiration hazard; Not applicable
Solid

Symptoms / effects, both acute and delayed Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SAFETY DATA SHEET

Nickel on silica-alumina, catalyst

Revision Date 30-Nov-2024

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects

The product contains following substances which are hazardous for the environment. Contains a substance which is: Very toxic to aquatic organisms. May cause long-term adverse effects in the environment. Do not allow material to contaminate ground water system.

| Component | Freshwater Fish | Water Flea | Freshwater Algae |
|-------------------|---|---|--|
| Nickel | LC50: > 100 mg/L, 96h (Brachydanio rerio) LC50: = 1.3 mg/L, 96h semi-static (Cyprinus carpio) LC50: = 10.4 mg/L, 96h static (Cyprinus carpio) | EC50: = 1 mg/L, 48h Static (Daphnia magna) EC50: > 100 mg/L, 48h (Daphnia magna) | EC50: 0.174 - 0.311 mg/L, 96h static (Pseudokirchneriella subcapitata) EC50: = 0.18 mg/L, 72h (Pseudokirchneriella subcapitata) |
| Nickel oxide | LC50: > 100 mg/L, 96h static (Brachydanio rerio) | EC50: > 100 mg/L, 48h (Daphnia magna) | EC50: > 127.3 mg/L, 72h (Pseudokirchneriella subcapitata) |
| Silica, amorphous | LC50: 5000 mg/L/96 h | EC50: 7600 mg/L/48h | EC50: 440 mg/L/72h |

12.2. Persistence and degradability

Persistence Degradability Degradation in sewage treatment plant

Product contains heavy metals. Discharge into the environment must be avoided. Special pre-treatment is necessary
Insoluble in water, May persist.
Not relevant for inorganic substances.
Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential

May have some potential to bioaccumulate; Product has a high potential to bioconcentrate

12.4. Mobility in soil

Spillage unlikely to penetrate soil Is not likely mobile in the environment due its low water solubility.

12.5. Results of PBT and vPvB assessment

No data available for assessment.

12.6. Endocrine disrupting properties

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance
This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and

SAFETY DATA SHEET

Nickel on silica-alumina, catalyst

Revision Date 30-Nov-2024

empty container away from heat and sources of ignition.

European Waste Catalogue (EWC) According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations.

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number UN3178
14.2. UN proper shipping name Flammable solid, inorganic, n.o.s.
Technical Shipping Name (Nickel powder)
14.3. Transport hazard class(es) 4.1
14.4. Packing group II

ADR

14.1. UN number UN3178
14.2. UN proper shipping name Flammable solid, inorganic, n.o.s.
Technical Shipping Name (Nickel powder)
14.3. Transport hazard class(es) 4.1
14.4. Packing group II

IATA

14.1. UN number UN3178
14.2. UN proper shipping name Flammable solid, inorganic, n.o.s.
Technical Shipping Name (Nickel powder)
14.3. Transport hazard class(es) 4.1
14.4. Packing group II

14.5. Environmental hazards No hazards identified

14.6. Special precautions for user No special precautions required.

14.7. Maritime transport in bulk according to IMO instruments Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

| Component | CAS No | EINECS | ELINCS | NLP | IECSC | TCSI | KECL | ENCS | ISHL |
|----------------|-----------|-----------|--------|-----|-------|------|----------|------|------|
| Nickel | 7440-02-0 | 231-111-4 | - | - | X | X | KE-25818 | X | - |
| Nickel oxide | 1313-99-1 | 215-215-7 | - | - | X | X | KE-25858 | X | X |
| Aluminum oxide | 1344-28-1 | 215-691-6 | - | - | X | X | KE-01012 | X | X |

SAFETY DATA SHEET

Nickel on silica-alumina, catalyst

Revision Date 30-Nov-2024

| Silica, amorphous | 7631-86-9 | 231-545-4 | - | - | X | X | KE-31032 | X | X |
|-------------------|-----------|-----------|---|-----|------|------|----------|-------|---|
| Component | CAS No | TSCA | TSCA Inventory notification - Active-Inactive | DSL | NDSL | AICS | NZIoC | PICCS | |
| Nickel | 7440-02-0 | X | ACTIVE | X | - | X | X | X | |
| Nickel oxide | 1313-99-1 | X | ACTIVE | X | - | X | X | X | |
| Aluminum oxide | 1344-28-1 | X | ACTIVE | X | - | X | X | X | |
| Silica, amorphous | 7631-86-9 | X | ACTIVE | X | - | X | X | X | |

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

| Component | CAS No | REACH (1907/2006) - Annex XIV - Substances Subject to Authorization | REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances | REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC) |
|-------------------|-----------|---|--|---|
| Nickel | 7440-02-0 | - | Use restricted. See entry 27. (see link for restriction details) Use restricted. See entry 75. (see link for restriction details) | - |
| Nickel oxide | 1313-99-1 | - | Use restricted. See entry 28. (see link for restriction details) Use restricted. See entry 75. (see link for restriction details) Use restricted. See entry 27. (see link for restriction details) | - |
| Aluminum oxide | 1344-28-1 | - | - | - |
| Silica, amorphous | 7631-86-9 | - | - | - |

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Seveso III Directive (2012/18/EC)

| Component | CAS No | Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification | Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements |
|-------------------|-----------|---|--|
| Nickel | 7440-02-0 | Not applicable | Not applicable |
| Nickel oxide | 1313-99-1 | Not applicable | 1 tonne |
| Aluminum oxide | 1344-28-1 | Not applicable | Not applicable |
| Silica, amorphous | 7631-86-9 | Not applicable | Not applicable |

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at

SAFETY DATA SHEET

Nickel on silica-alumina, catalyst

Revision Date 30-Nov-2024

work .

Take note of Dir 76/769/EEC relating to restrictions on the marketing and use of certain dangerous substances and preparations

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

Water endangering class = 2 (self classification)

| Component | Germany - Water Classification (AwSV) | Germany - TA-Luft Class |
|-------------------|---------------------------------------|--|
| Nickel | WGK2 | Class II : 0.5 mg/m ³ (Massenkonzentration) Krebserzeugende Stoffe - Class II : 0.5 mg/m ³ (Massenkonzentration) |
| Nickel oxide | WGK1 | |
| Aluminum oxide | nwg | |
| Silica, amorphous | nwg | |

| Component | France - INRS (Tables of occupational diseases) |
|-------------------|---|
| Nickel oxide | Tableaux des maladies professionnelles (TMP) - RG 37,RG 37bis |
| Silica, amorphous | Tableaux des maladies professionnelles (TMP) - RG 25 |

| Component | Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81) | Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC) | Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure |
|------------------------------|--|---|---|
| Nickel 7440-02-0 (50.0) | Prohibited and Restricted Substances | | |

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H228 - Flammable solid
H317 - May cause an allergic skin reaction
H350 - May cause cancer
H350i - May cause cancer by inhalation
H372 - Causes damage to organs through prolonged or repeated exposure
H413 - May cause long lasting harmful effects to aquatic life
H351 - Suspected of causing cancer

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer
Predicted No Effect Concentration (PNEC)

SAFETY DATA SHEET

Nickel on silica-alumina, catalyst

Revision Date 30-Nov-2024

RPE - Respiratory Protective Equipment
LC50 - Lethal Concentration 50%
NOEC - No Observed Effect Concentration
PBT - Persistent, Bioaccumulative, Toxic

LD50 - Lethal Dose 50%
EC50 - Effective Concentration 50%
POW - Partition coefficient Octanol:Water
vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data

Health Hazards Calculation method

Environmental hazards Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Prepared By Health, Safety and Environmental Department

Revision Date 30-Nov-2024

Revision Summary Not applicable.

This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet