

according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended

Creation Date 21-May-2010 Revision Date 10-Feb-2024 Revision Number 3

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product Description: <u>Aluminum sec-butoxide</u>

Cat No. : A13044

Synonyms Aluminium sec-butoxide

 CAS No
 2269-22-9

 EC No
 218-871-2

 Molecular Formula
 C12 H27 Al O3

REACH registration number -

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

Avocado Research Chemicals Ltd. (Part of Thermo Fisher Scientific)

Shore Road, Heysham Lancashire, LA3 2XY, United Kingdom

Office Tel: +44 (0) 1524 850506 Office Fax: +44 (0) 1524 850608

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

## **SECTION 2: HAZARDS IDENTIFICATION**

## 2.1. Classification of the substance or mixture

CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

**Physical hazards** 

Flammable liquids Category 3 (H226)

**Health hazards** 

ALFAAA13044

#### Aluminum sec-butoxide Revision Date 10-Feb-2024

Serious Eye Damage/Eye Irritation Specific target organ toxicity - (single exposure) Category 2 (H319) Category 3 (H335) (H336)

#### **Environmental hazards**

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

#### 2.2. Label elements



#### Signal Word

#### Warning

#### **Hazard Statements**

H226 - Flammable liquid and vapor

H319 - Causes serious eye irritation

H335 - May cause respiratory irritation

H336 - May cause drowsiness or dizziness

#### **Precautionary Statements**

P280 - Wear eye protection/ face protection

P337 + P313 - If eye irritation persists: Get medical advice/attention

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P312 - Call a POISON CENTER or doctor if you feel unwell

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

#### 2.3. Other hazards

Decomposes in contact with water

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB)

This product does not contain any known or suspected endocrine disruptors

## **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

## 3.1. Substances

Component	CAS No	EC No	Weight %	CLP Classification - According to
				GB-CLP Regulations UK SI 2019/720 and
				UK SI 2020/1567
2-Butanol, aluminum salt	2269-22-9	EEC No. 218-871-2	>95	Flam. Liq. 3 (H226)
				Eye Irrit. 2 (H319)
				STOT SE 3 (H335)
				STOT SE 3 (H336)

REACH registration number	-

Aluminum sec-butoxide Revision Date 10-Feb-2024

Full text of Hazard Statements: see section 16

## **SECTION 4: FIRST AID MEASURES**

#### 4.1. Description of first aid measures

**General Advice** If symptoms persist, call a physician.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists,

call a physician.

**Ingestion** Clean mouth with water and drink afterwards plenty of water.

**Inhalation** Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

#### 4.2. Most important symptoms and effects, both acute and delayed

. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated

#### 4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically. Symptoms may be delayed.

## **SECTION 5: FIREFIGHTING MEASURES**

#### 5.1. Extinguishing media

#### Suitable Extinguishing Media

CO<sub>2</sub>, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.

#### Extinguishing media which must not be used for safety reasons

Water.

## 5.2. Special hazards arising from the substance or mixture

Flammable. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Vapors may form explosive mixtures with air. Reacts violently with water.

#### **Hazardous Combustion Products**

Carbon monoxide (CO), Carbon dioxide (CO2), Burning produces obnoxious and toxic fumes.

#### 5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

## 6.1. Personal precautions, protective equipment and emergency procedures

#### Aluminum sec-butoxide Revision Date 10-Feb-2024

Ensure adequate ventilation. Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges.

#### 6.2. Environmental precautions

Should not be released into the environment.

#### 6.3. Methods and material for containment and cleaning up

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material. Do not expose spill to water. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

#### 6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

## **SECTION 7: HANDLING AND STORAGE**

#### 7.1. Precautions for safe handling

Do not get in eyes, on skin, or on clothing. Wear personal protective equipment/face protection. Ensure adequate ventilation. Avoid ingestion and inhalation. Do not allow contact with water. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Take precautionary measures against static discharges.

#### **Hygiene Measures**

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

## 7.2. Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and flame. Corrosives area. Flammables area. Keep under nitrogen. Keep container tightly closed in a dry and well-ventilated place. Keep away from water or moist air.

Technical Rules for Hazardous Substances (TRGS) 510 Class 3 Storage Class (LGK) (Germany)

#### 7.3. Specific end use(s)

Use in laboratories

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

### 8.1. Control parameters

#### **Exposure limits**

This product, as supplied, does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies

#### **Biological limit values**

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

#### Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Aluminum sec-butoxide Revision Date 10-Feb-2024

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
2-Butanol, aluminum salt				DNEL = 300mg/kg
2269-22-9 ( >95 )				bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
2-Butanol, aluminum salt 2269-22-9 ( >95 )				DNEL = 161mg/m <sup>3</sup>

#### **Predicted No Effect Concentration (PNEC)**

No information available.

#### 8.2. Exposure controls

#### **Engineering Measures**

Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

## Personal protective equipment

**Eye Protection** Goggles (European standard - EN 166)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Nitrile rubber	See manufacturers	-	EN 374	(minimum requirement)
Viton (R)	recommendations			
Neoprene				
Natural rubber				
PVC				

Skin and body protection Long sleeved clothing.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

**Respiratory Protection** When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits

are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: Organic gases and vapours filter Type A Brown conforming to

EN14387

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure

limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN

141

When RPE is used a face piece Fit Test should be conducted

Aluminum sec-butoxide Revision Date 10-Feb-2024

**Environmental exposure controls** No information available.

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

## 9.1. Information on basic physical and chemical properties

Physical State Viscous liquid Liquid

Appearance Light yellow

Odor
Odor No information available
No data available
Melting Point/Range
No data available
No data available
No data available

**Boiling Point/Range** 200 - 206 °C / 392 - 402.8 °F @ 30 mmHg

Flammability (liquid) Flammable On basis of test data

Flammability (solid,gas) Not applicable Liquid

Explosion Limits Lower 1.7 Vol%

Upper 9.8 Vol%

Flash Point 27 °C / 80.6 °F Method - No information available

Autoignition Temperature406 °C / 762.8 °FDecomposition TemperatureNo data availablepHNo information availableViscosity1800 mPa.s at 20 °C

Water Solubility Decomposes

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Vapor Pressure 23 hPa @ 195 °C

**Density / Specific Gravity** 0.960

Bulk DensityNot applicableLiquidVapor DensityNo data available(Air = 1.0)

Particle characteristics Not applicable (liquid)

9.2. Other information

Molecular Formula C12 H27 Al O3 Molecular Weight 246.33

**Explosive Properties** explosive air/vapour mixtures possible

## **SECTION 10: STABILITY AND REACTIVITY**

10.1. Reactivity

No

10.2. Chemical stability

Moisture sensitive. Air sensitive.

10.3. Possibility of hazardous reactions

**Hazardous Polymerization** Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing. Reacts violently with water.

10.4. Conditions to avoid

Exposure to air. Incompatible products. Exposure to moist air or water. Keep away from

open flames, hot surfaces and sources of ignition. Exposure to moisture.

10.5. Incompatible materials

Strong oxidizing agents. Strong acids. Halogens. Metals.

#### 10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Burning produces obnoxious and toxic

Revision Date 10-Feb-2024 Aluminum sec-butoxide

fumes.

## **SECTION 11: TOXICOLOGICAL INFORMATION**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Product Information**

(a) acute toxicity;

Oral No data available **Dermal** No data available Inhalation No data available

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
2-Butanol, aluminum salt	>2000 mg/kg (Rat)	>2000 mg/kg (Rabbit)	-

(b) skin corrosion/irritation; No data available

(c) serious eye damage/irritation; Category 2

(d) respiratory or skin sensitization;

Respiratory No data available Skin No data available

No data available (e) germ cell mutagenicity;

No data available (f) carcinogenicity;

There are no known carcinogenic chemicals in this product

No data available (g) reproductive toxicity;

Category 3 (h) STOT-single exposure;

Results / Target organs Respiratory system, Central nervous system (CNS).

No data available (i) STOT-repeated exposure;

No information available. **Target Organs** 

(j) aspiration hazard; No data available

Other Adverse Effects The toxicological properties have not been fully investigated.

delayed

Symptoms / effects, both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of

perforation. Product is a corrosive material. Use of gastric lavage or emesis is

contraindicated. Possible perforation of stomach or esophagus should be investigated.

#### 11.2. Information on other hazards

Assess endocrine disrupting properties for human health. This product does not contain any **Endocrine Disrupting Properties** 

known or suspected endocrine disruptors.

## **SECTION 12: ECOLOGICAL INFORMATION**

Revision Date 10-Feb-2024 Aluminum sec-butoxide

12.1. Toxicity

**Ecotoxicity effects** Do not empty into drains. Reacts with water so no ecotoxicity data for the substance is

available.

12.2. Persistence and degradability

treatment plant

Persistence Persistence is unlikely, based on information available.

Degradability Decomposes in contact with water.

Degradation in sewage Decomposes in contact with water. No information available.

12.3. Bioaccumulative potential Product does not bioaccumulate due to reaction with water

Decomposes in contact with water Is not likely mobile in the environment. 12.4. Mobility in soil

Decomposes in contact with water. Substance is not considered persistent, 12.5. Results of PBT and vPvB

bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB). <u>assessment</u>

12.6. Endocrine disrupting

properties

**Endocrine Disruptor Information** This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

**Persistent Organic Pollutant** This product does not contain any known or suspected substance **Ozone Depletion Potential** This product does not contain any known or suspected substance

## **SECTION 13: DISPOSAL CONSIDERATIONS**

13.1. Waste treatment methods

Waste from Residues/Unused Waste is classified as hazardous. Dispose of in accordance with the European Directives **Products** 

on waste and hazardous waste. Dispose of in accordance with local regulations.

**Contaminated Packaging** Dispose of this container to hazardous or special waste collection point. Empty containers

retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and

empty container away from heat and sources of ignition.

According to the European Waste Catalog, Waste Codes are not product specific, but **European Waste Catalogue (EWC)** 

application specific.

Waste codes should be assigned by the user based on the application for which the product Other Information

was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with

local regulations.

## **SECTION 14: TRANSPORT INFORMATION**

IMDG/IMO

14.1. UN number UN1993

Flammable liquid, n.o.s. 14.2. UN proper shipping name **Technical Shipping Name** 2-Butanol, aluminum salt

Aluminum sec-butoxide Revision Date 10-Feb-2024

14.3. Transport hazard class(es) 3 14.4. Packing group III

<u>ADR</u>

**14.1. UN number** UN1993

14.2. UN proper shipping nameFlammable liquid, n.o.s.Technical Shipping Name2-Butanol, aluminum salt

14.3. Transport hazard class(es) 3 14.4. Packing group III

<u>IATA</u>

**14.1. UN number** UN1993

14.2. UN proper shipping nameFlammable liquid, n.o.s.Technical Shipping Name2-Butanol, aluminum salt

14.3. Transport hazard class(es) 3 14.4. Packing group III

14.5. Environmental hazards No hazards identified

**14.6. Special precautions for user** No special precautions required.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable, packaged goods

## **SECTION 15: REGULATORY INFORMATION**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **International Inventories**

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
2-Butanol, aluminum salt	2269-22-9	218-871-2		-	X	X	KE-03873	Χ	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
2-Butanol, aluminum salt	2269-22-9	X	ACTIVE	X	-	Х	Х	X

Legend: X - Listed '-' - Not Listed KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

## Authorisation/Restrictions according to EU REACH Not applicable

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization		REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
2-Butanol, aluminum salt	2269-22-9	-	-	-

#### Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) -	Seveso III Directive (2012/18/EC) -
		Qualifying Quantities for Major Accident	<b>Qualifying Quantities for Safety Report</b>
		Notification	Requirements
2-Butanol, aluminum salt	2269-22-9	Not applicable	Not applicable

Aluminum sec-butoxide Revision Date 10-Feb-2024

#### import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

## **National Regulations**

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

**WGK Classification** 

Water endangering class = 2 (self classification)

#### 15.2. Chemical safety assessment

A Chemical Safety Assessment/Report (CSA/CSR) has not been conducted

## **SECTION 16: OTHER INFORMATION**

#### Full text of H-Statements referred to under sections 2 and 3

H319 - Causes serious eye irritation

H335 - May cause respiratory irritation

H336 - May cause drowsiness or dizziness

H226 - Flammable liquid and vapor

### Legend

**CAS** - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

**IECSC** - Chinese Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

WEL - Workplace Exposure Limit

**ACGIH** - American Conference of Governmental Industrial Hygienists

**DNEL** - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

**OECD** - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

TSCA - United States Toxic Substances Control Act Section 8(b)

Substances List

**ENCS** - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

Aluminum sec-butoxide Revision Date 10-Feb-2024

Suppliers safety data sheet. Chemadvisor - LOLI, Merck index, RTECS

#### Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts. Chemical incident response training.

Prepared By Health, Safety and Environmental Department

**Creation Date** 21-May-2010 **Revision Date** 10-Feb-2024

**Revision Summary** New emergency telephone response service provider.

## This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.

**Disclaimer** 

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

## **End of Safety Data Sheet**