

according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended

Creation Date 07-Oct-2010 Revision Date 17-May-2024 Revision Number 12

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: Methyl vinyl ketone, stabilized

Cat No. : 128000000; 128000010; 128000025; 128000050

Synonyms 3-Buten-2-one; MVK

 CAS No
 78-94-4

 EC No
 201-160-6

 Molecular Formula
 C4 H6 O

REACH registration number 01-2120090431-63

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended UseLaboratory chemicals.

Sector of use SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

Product category PC21 - Laboratory chemicals

Process categories PROC15 - Use as a laboratory reagent

Environmental release category ERC6a - Industrial use resulting in manufacture of another substance (use of intermediates)

Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

UK entity/business name

Fisher Scientific UK Bishop Meadow Road,

Loughborough, Leicestershire LE11 5RG, United Kingdom

EU entity/business name Thermo Fisher Scientific

Janssen Pharmaceuticalaan 3a, 2440 Geel, Belgium

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

GHS Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Physical hazards

Methyl vinyl ketone, stabilized

Revision Date 17-May-2024

Flammable liquids	Category 2 (H225)
Health hazards	
Acute oral toxicity Acute dermal toxicity Acute Inhalation Toxicity - Vapors Skin Corrosion/Irritation Serious Eye Damage/Eye Irritation Skin Sensitization Specific target organ toxicity - (repeated exposure)	Category 2 (H300) Category 1 (H310) Category 1 (H330) Category 1 B (H314) Category 1 (H318) Category 1 (H317) Category 2 (H373)
Environmental hazards Acute aquatic toxicity Chronic aquatic toxicity	Category 1 (H400) Category 1 (H410)

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

- H225 Highly flammable liquid and vapor
- H314 Causes severe skin burns and eye damage
- H317 May cause an allergic skin reaction
- H373 May cause damage to organs through prolonged or repeated exposure
- H410 Very toxic to aquatic life with long lasting effects
- H300 + H310 + H330 Fatal if swallowed, in contact with skin or if inhaled

Precautionary Statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- P280 Wear protective gloves/protective clothing/eye protection/face protection
- P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
- P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
- P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- P310 Immediately call a POISON CENTER or doctor/physician

2.3. Other hazards

This product does not contain any known or suspected endocrine disruptors

Revision Date 17-May-2024

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS No	EC No	Weight %	GHS Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567
Methyl vinyl ketone	78-94-4	EEC No. 201-160-6	95	Flam. Liq. 2 (H225) Skin Corr. 1B (H314) Eye Dam. 1 (H318) Acute Tox. 2 (H300) Acute Tox. 1 (H310) Acute Tox. 1 (H330) Skin Sens. 1 (H317) STOT RE 2 (H373) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)
Acetic acid	64-19-7	200-580-7	0.4-1	Flam. Liq. 3 (H226) Skin Corr. 1A (H314) Eye Dam. 1 (H318)
Acetonitrile	75-05-8	200-835-2	< 0.7	Flam. Liq. 2 (H225) Acute Tox. 4 (H302) Acute Tox. 4 (H312) Eye Irrit. 2 (H319) Acute Tox. 4 (H332)
Hydroquinone	123-31-9	EEC No. 204-617-8	0.3-0.5	Acute Tox. 4 (H302) Eye Dam. 1 (H318) Skin Sens. 1 (H317) Muta. 2 (H341) Carc. 2 (H351) Aquatic Acute 1 (H400)
Water	7732-18-5	231-791-2	3	- ` '

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Methyl vinyl ketone	-	1	-
Acetic acid	Skin Corr. 1A (H314) :: C>=90% Skin Corr. 1B (H314) :: 25%<=C<90% Eye Irrit. 2 (H319) :: 10%<=C<25% Skin Irrit. 2 (H315) :: 10%<=C<25%	-	-
Hydroquinone	-	10	-

Component	ECHA (RAC) ATE (Oral)	ECHA (RAC) ATE (Dermal)	ECHA (RAC) ATE (Inhalation)
Acetonitrile	ATE = 617 mg/kg	-	-

ECHA (RAC) - Committee for Risk Assessment - European CHemicals Agency ATE - Acute Toxiciy Estimate; mg/kg bw - milligrams per kilogram of body weight

REACH registration number	01-2120090431-63

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice Show this safety data sheet to the doctor in attendance. Immediate medical attention is

required.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In

Methyl vinyl ketone, stabilized

the case of contact with eyes, rinse immediately with plenty of water and seek medical

Revision Date 17-May-2024

advice.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Immediate medical

attention is required.

Ingestion Do NOT induce vomiting. Call a physician or poison control center immediately.

Inhalation If not breathing, give artificial respiration. Do not use mouth-to-mouth method if victim

ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Remove to fresh

air. Immediate medical attention is required.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns by all exposure routes. May cause allergic skin reaction. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Water mist may be used to cool closed containers. CO₂, dry chemical, dry sand, alcohol-resistant foam.

Extinguishing media which must not be used for safety reasons

No information available.

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Do not allow run-off from fire-fighting to enter drains or water courses.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO2), Thermal decomposition can lead to release of irritating gases and vapors.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Methyl vinyl ketone, stabilized

Revision Date 17-May-2024

Use personal protective equipment as required. Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Corrosives area. Keep away from heat, sparks and flame. To maintain product quality: Keep refrigerated. Keep at temperatures below 10°C.

Technical Rules for Hazardous Substances (TRGS) 510 Class 3 Storage Class (LGK) (Germany)

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

Component	The United Kingdom	European Union	Ireland
Methyl vinyl ketone			STEL: 0.2 ppm 15 min
			Skin
Acetic acid	STEL: 37 mg/m ³	TWA: 25 mg/m ³ (8h)	TWA: 20 ppm 8 hr.
	STEL: 15 ppm	TWA: 10 ppm (8h)	TWA: 50 mg/m ³ 8 hr.

Methyl vinyl ketone, stabilized

Revision Date 17-May-2024

	TWA: 10 ppm TWA: 25 mg/m³	STEL: 50 mg/m³ (15min) STEL: 20 ppm (15min)	STEL: 20 ppm 15 min STEL: 50 mg/m³ 15 min
Acetonitrile	STEL: 60 ppm 15 min STEL: 102 mg/m³ 15 min TWA: 40 ppm 8 hr TWA: 68 mg/m³ 8 hr	TWA: 40 ppm (8hr) TWA: 70 mg/m³ (8hr) Skin	TWA: 40 ppm 8 hr. TWA: 70 mg/m³ 8 hr. STEL: 120 ppm 15 min STEL: 310 mg/m³ 15 min Skin
Hydroquinone	STEL: 1.5 mg/m ³ 15 min TWA: 0.5 mg/m ³ 8 hr		TWA: 0.5 mg/m ³ 8 hr. STEL: 1.5 mg/m ³ 15 min

Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Derived No Effect Level (DNEL) / **Derived Minimum Effect Level (DMEL)** See table for values

Component	Acute effects local	Acute effects	Chronic effects local	Chronic effects
	(Dermal)	systemic (Dermal)	(Dermal)	systemic (Dermal)
Acetonitrile				DNEL = 32.2mg/kg
75-05-8 (< 0.7)				bw/day
Hydroquinone				DNEL = 3.33mg/kg
123-31-9 (0.3-0.5)				bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Acetic acid 64-19-7 (0.4-1)	DNEL = 25mg/m ³		DNEL = 25mg/m ³	
Acetonitrile 75-05-8 (< 0.7)	DNEL = 40.6 ppm (68 mg/m³)	DNEL = 40.6 ppm (68 mg/m³)	DNEL = 40.6 ppm (68 mg/m³)	DNEL = 40.6 ppm (68 mg/m ³)
Hydroquinone 123-31-9 (0.3-0.5)				DNEL = 2.1mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water	Water Intermittent	Microorganisms in	Soil (Agriculture)
		sediment		sewage treatment	
Acetic acid	PNEC = 3.058mg/L	PNEC =	PNEC = 30.58mg/L	PNEC = 85mg/L	PNEC = 0.47mg/kg
64-19-7 (0.4-1)		11.36mg/kg		-	soil dw
		sediment dw			
Acetonitrile	PNEC = 10mg/L	PNEC = 7.53mg/kg	PNEC = 10mg/L	PNEC = 32mg/L	PNEC = 2.41 mg/kg
75-05-8 (< 0.7)		sediment dw		-	soil dw
Hydroquinone	PNEC = $0.57\mu g/L$	$PNEC = 4.9 \mu g/kg$	PNEC = 1.34µg/L	PNEC = 0.71mg/L	$PNEC = 0.64 \mu g/kg$
123-31-9 (0.3-0.5)		sediment dw			soil dw

Component	Marine water	Marine water	Marine water	Food chain	Air
		sediment	intermittent		
Acetic acid	PNEC =	PNEC =			
64-19-7 (0.4-1)	0.3058mg/L	1.136mg/kg			
	-	sediment dw			
Acetonitrile	PNEC = 1mg/L				
75-05-8 (< 0.7)	-				
Hydroquinone	$PNEC = 0.057 \mu g/L$	$PNEC = 0.49 \mu g/kg$			
123-31-9 (0.3-0.5)		sediment dw			

8.2. Exposure controls

Methyl vinyl ketone, stabilized

Engineering Measures

Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eve Protection Goggles (European standard - EN 166)

Hand Protection Protective gloves

PVC

Skin and body protection Long sleeved clothing.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits Large scale/emergency use

are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: Organic gases and vapours filter Type A Brown conforming to

EN14387

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure Small scale/Laboratory use

limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls Prevent product from entering drains. Do not allow material to contaminate ground water

system. Local authorities should be advised if significant spillages cannot be contained.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State Liquid

Light yellow **Appearance** Irritating pungent Odor **Odor Threshold** 0.2 ppm

Melting Point/Range No data available **Softening Point** No data available **Boiling Point/Range** 80 °C / 176 °F Flammability (liquid) Highly flammable

On basis of test data Flammability (solid, gas) Not applicable

Liquid

@ 760 mmHa

ACR12800

Revision Date 17-May-2024

Methyl vinyl ketone, stabilized Revision Date 17-May-2024

Explosion Limits Lower 2.1 vol%

Upper 15.6 vol%

Flash Point -7 °C / 19.4 °F Method - No information available

Autoignition Temperature 370 °C / 698 °F **Decomposition Temperature** No data available pН Not applicable

Viscosity Dynamic 0.81 mPa.s (70 °C)

Water Solubility Miscible

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Component log Pow Acetic acid -0.2 Acetonitrile -0.34Hydroquinone 0.59

Vapor Pressure 130 mbar @ 28 °C 0.864 g/cm3 @20°C **Density / Specific Gravity**

Bulk Density Not applicable Liquid **Vapor Density** 2.4 (Air = 1.0)

Particle characteristics Not applicable (liquid)

9.2. Other information

Molecular Formula C4 H6 O **Molecular Weight** 70.09

Explosive Properties Vapors may form explosive mixtures with air >50°C (all packages)

Self-accelerating polymerisation

temperature (SAPT)

Surface tension 24 mN/m

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity Yes; Hazardous polymerization may occur

10.2. Chemical stability

Light sensitive, heat sensitive,

10.3. Possibility of hazardous reactions

Hazardous Polymerization Polymerization can occur. **Hazardous Reactions** None under normal processing.

10.4. Conditions to avoid

Excess heat. Exposure to light. Keep away from open flames, hot surfaces and sources of

ignition. Incompatible products.

10.5. Incompatible materials

Oxidizing agent. Reducing Agent. oxygen. Bases. Amines. Ammonia.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO₂). Thermal decomposition can lead to release

of irritating gases and vapors.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Methyl vinyl ketone, stabilized

Product Information

(a) acute toxicity;

Oral Category 2 Dermal Category 1 Inhalation Category 1

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methyl vinyl ketone	LD50 = 23.1 mg/kg (Rat)	LD50 = 35 mg/kg (Rat)	$LC50 = 7 \text{ mg/m}^3 \text{ (Rat) 4 h}$
Acetic acid	3310 mg/kg (Rat)	-	> 40 mg/L (Rat) 4 h
Acetonitrile	450-787 mg/kg (Rat) 2460 mg/kg (Rat)	> 2000 mg/kg(Rabbit)	LC50 = 3587 ppm (6.022 mg/l) (Mouse) 4h LC50 = 16,000 ppm (26.8 mg/l) (Rat) 4h
Hydroquinone	LD50 = 298 mg/kg (Rat)	LD50 = 74800 mg/kg (Rabbit)	-
Water	-	-	- -

Component	ECHA (RAC) ATE (Oral)	ECHA (RAC) ATE (Dermal)	ECHA (RAC) ATE (Inhalation)
Acetonitrile	ATE = 617 mg/kg	=	-

ECHA (RAC) - Committee for Risk Assessment - European CHemicals Agency ATE - Acute Toxiciy Estimate; mg/kg bw - milligrams per kilogram of body weight

Category 1 B (b) skin corrosion/irritation;

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;

Respiratory

Based on available data, the classification criteria are not met

Skin Category 1

May cause sensitization by skin contact

Based on available data, the classification criteria are not met (e) germ cell mutagenicity;

(f) carcinogenicity; Based on available data, the classification criteria are not met

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
Hydroquinone			Cat. 2	

Based on available data, the classification criteria are not met (g) reproductive toxicity;

(h) STOT-single exposure; Based on available data, the classification criteria are not met

Category 2 (i) STOT-repeated exposure;

Target Organs Kidney, Central nervous system (CNS), Lungs.

(j) aspiration hazard; Based on available data, the classification criteria are not met

delayed

Symptoms / effects, both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Product is a corrosive material. Use of gastric lavage or

emesis is contraindicated. Possible perforation of stomach or esophagus should be

Revision Date 17-May-2024

Revision Date 17-May-2024

investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing.

11.2. Information on other hazards

Endocrine Disrupting Properties

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity Ecotoxicity effects

The product contains following substances which are hazardous for the environment. Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Acetic acid	Pimephales promelas: LC50 = 88 mg/L/96h Lepomis macrochirus: LC50 = 75 mg/L/96h	Ğ	-
Acetonitrile	LC50: = 1850 mg/L, 96h static (Lepomis macrochirus) LC50: = 1000 mg/L, 96h static (Pimephales promelas) LC50: 1600 - 1690 mg/L, 96h flow-through (Pimephales promelas) LC50: = 1650 mg/L, 96h static (Poecilia reticulata)		
Hydroquinone	LC50: 0.1 - 0.18 mg/L, 96h static (Pimephales promelas) LC50: = 0.17 mg/L, 96h (Brachydanio rerio) LC50: = 0.044 mg/L, 96h flow-through (Pimephales promelas) LC50: = 0.044 mg/L, 96h flow-through (Oncorhynchus mykiss)		EC50: = 0.335 mg/L, 72h (Pseudokirchneriella subcapitata)

Component	Microtox	M-Factor
Methyl vinyl ketone		1
Acetic acid	Photobacterium phosphoreum: EC50 = 8.8 mg/L/15 min Photobacterium phosphoreum: EC50 = 8.8 mg/L/25 min Photobacterium phosphoreum: EC50 = 8.8 mg/L/5 min	
Acetonitrile	EC50 = 28000 mg/L 48 h EC50 = 73 mg/L 24 h EC50 = 7500 mg/L 15 h	
Hydroquinone	EC50 = 0.038 mg/L 15 min EC50 = 0.0382 mg/L 30 min EC50 = 0.042 mg/L 5 min EC50 = 23.75 mg/L 60 min	10

Methyl vinyl ketone, stabilized Revision Date 17-May-2024

12.2. Persistence and degradability

Not readily biodegradable

Persistence is unlikely, based on information available. **Persistence**

Degradation in sewage Contains substances known to be hazardous to the environment or not degradable in waste

treatment plant water treatment plants.

12.3. Bioaccumulative potential Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Acetic acid	-0.2	No data available
Acetonitrile	-0.34	No data available
Hydroquinone	0.59	40 dimensionless

The product contains volatile organic compounds (VOC) which will evaporate easily from all 12.4. Mobility in soil

surfaces Will likely be mobile in the environment due to its volatility. Disperses rapidly in

air

Surface tension 24 mN/m

12.5. Results of PBT and vPvB

assessment

No data available for assessment.

12.6. Endocrine disrupting

properties

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused

Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers

retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and

empty container away from heat and sources of ignition.

According to the European Waste Catalog, Waste Codes are not product specific, but **European Waste Catalogue (EWC)**

application specific.

Other Information Do not flush to sewer. Waste codes should be assigned by the user based on the

application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH

and harm aquatic organisms. Do not let this chemical enter the environment.

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number UN1251

14.2. UN proper shipping name METHYL VINYL KETONE, STABILIZED

Methyl vinyl ketone, stabilized Revision Date 17-May-2024

14.3. Transport hazard class(es) 6.1 Subsidiary Hazard Class 3, 8 14.4. Packing group I

ADR

14.1. UN number UN1251

14.2. UN proper shipping name METHYL VINYL KETONE, STABILIZED

14.3. Transport hazard class(es)6.1Subsidiary Hazard Class3, 814.4. Packing groupI

IATA FORBIDDEN FOR IATA TRANSPORT

14.1. UN number UN1251

14.2. UN proper shipping name METHYL VINYL KETONE, STABILIZED FORBIDDEN FOR IATA TRANSPORT

14.3. Transport hazard class(es)6.1Subsidiary Hazard Class3, 814.4. Packing groupI

<u>14.5. Environmental hazards</u> Dangerous for the environment

Product is a marine pollutant according to the criteria set by IMDG/IMO

14.6. Special precautions for user Storage conditions in Section 7 should also be met during transportation. Cooled

transportation <10°C is recommended to ensure shelf-life. Inhibitors have been added to stabilize this product. Inhibitor levels should be maintained. Hazardous polymerization may

occur upon depletion of inhibitor.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

China, X = listed, Australia, U.S.A. (TSCA), Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Australia (AICS), Korea (KECL), China (IECSC), Japan (ENCS), Philippines (PICCS), Taiwan (TCSI), Japan (ISHL), New Zealand (NZIoC), Japan (ISHL). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Methyl vinyl ketone	78-94-4	201-160-6	-	-	X	X	KE-04112	X	Χ
Acetic acid	64-19-7	200-580-7	-	-	Х	X	X	X	Χ
Acetonitrile	75-05-8	200-835-2	-	-	Х	X	KE-00067	X	Х
Hydroquinone	123-31-9	204-617-8	-	-	Х	Χ	KE-35112	X	X
Water	7732-18-5	231-791-2	-	-	Х	Х	KE-35400	Х	_

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Methyl vinyl ketone	78-94-4	X	ACTIVE	-	X	Х	Х	Х
Acetic acid	64-19-7	X	ACTIVE	Х	-	X	Х	X
Acetonitrile	75-05-8	X	ACTIVE	Х	-	Х	Х	X
Hydroquinone	123-31-9	X	ACTIVE	Х	ı	X	Х	X
Water	7732-18-5	Х	ACTIVE	Х	-	Х	Х	Х

Legend: X - Listed '-' - Not Listed KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

Methyl vinyl ketone, stabilized

Revision Date 17-May-2024

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Methyl vinyl ketone	78-94-4	-	-	-
Acetic acid	64-19-7	-	Use restricted. See item 75. (see link for restriction details)	-
Acetonitrile	75-05-8	-	Use restricted. See item 75. (see link for restriction details)	-
Hydroquinone	123-31-9	-	Use restricted. See item 75. (see link for restriction details)	-
Water	7732-18-5	-	-	-

REACH links

https://echa.europa.eu/substances-restricted-under-reach

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Methyl vinyl ketone	78-94-4	Not applicable	Not applicable
Acetic acid	64-19-7	Not applicable	Not applicable
Acetonitrile	75-05-8	Not applicable	Not applicable
Hydroquinone	123-31-9	Not applicable	Not applicable
Water	7732-18-5	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification Water endangering class = 3 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Methyl vinyl ketone	WGK3	
Acetic acid	WGK1	Class II: 0.10 g/m³ (Massenkonzentration)
Acetonitrile	WGK2	
Hydroquinone	WGK3	Class I: 20 mg/m³ (Massenkonzentration)

Methyl vinyl ketone, stabilized

Hydroquinone

Component	France - INRS (Tables of occupational diseases)
Acetonitrile	Tableaux des maladies professionnelles (TMP) - RG 84

Tableaux des maladies professionnelles (TMP) - RG 65

	Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
ſ	Acetic acid	Prohibited and Restricted	Group I	
L	64-19-7 (0.4-1)	Substances		
Ī	Hydroquinone	Prohibited and Restricted		
- 1	123-31-9 (0.3-0.5)	Substances		

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H225 - Highly flammable liquid and vapor

H226 - Flammable liquid and vapor

H300 - Fatal if swallowed

H302 - Harmful if swallowed

H310 - Fatal in contact with skin

H312 - Harmful in contact with skin

H314 - Causes severe skin burns and eye damage

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H319 - Causes serious eye irritation

H330 - Fatal if inhaled

H332 - Harmful if inhaled

H341 - Suspected of causing genetic defects

H351 - Suspected of causing cancer

H373 - May cause damage to organs through prolonged or repeated exposure

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

Legend

CAS - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

Revision Date 17-May-2024

Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

Page 14/15

ENCS - Japanese Existing and New Chemical Substances AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

Methyl vinyl ketone, stabilized

Revision Date 17-May-2024

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code Shins

OECD - Organisation for Economic Co-operation and Development

ADR - European Agreement Concerning the International Carriage of

BCF - Bioconcentration factor

Dangerous Goods by Road

ATE - Acute Toxicity Estimate VOC - (Volatile Organic Compound)

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data **Health Hazards** Calculation method **Environmental hazards** Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Creation Date 07-Oct-2010 **Revision Date** 17-May-2024

SDS sections updated, 2, 11. **Revision Summary**

This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet