

according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended

Creation Date 01-Sep-2009

Revision Date 20-Oct-2023

Revision Number 19

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: Cat No. :	<u>Propan-2-ol</u> P/7490/08, P/7490/15, P/7490/17, P/7490/21, P/7490/FP21, P/7490/25, P/7490/27, P/7490/DH25, P/7490/MC15, P/7490/PB08, P/7490/PB17, P/7490/PC24, P/7490/PC25, P/7490/21RSS, P/7490/24RSS, P/7490/25RSS, P/7490/34RSS, P/7490/27RSS
Synonyms	2-Propanol; IPA; Isopropyl alcohol; Propan-2-ol; Isopropanol
Index No	603-117-00-0
CAS No	67-63-0
EC No	200-661-7
Molecular Formula	C3 H8 O
REACH registration number	01-2119457558-25

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Sector of use	Laboratory chemicals. SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites
Product category	PC21 - Laboratory chemicals
Process categories	PROC15 - Use as a laboratory reagent
Environmental release category	ERC6a - Industrial use resulting in manufacture of another substance (use of intermediates)
Uses advised against	No Information available

1.3. Details of the supplier of the safety data sheet

Company

UK entity/business name

Fisher Scientific UK Bishop Meadow Road, Loughborough, Leicestershire LE11 5RG, United Kingdom

EU entity/business name

Thermo Fisher Scientific Janssen Pharmaceuticalaan 3a 2440 Geel, Belgium

E-mail address

begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

Tel: 01509 231166 Chemtrec US: (800) 424-9300 Chemtrec EU: 001-703-527-3887

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Propan-2-ol

CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Physical hazards

Flammable liquids

Health hazards

Serious Eye Damage/Eye Irritation Specific target organ toxicity - (single exposure)

Environmental hazards Based on available data, the classification criteria are not met Category 2 (H225)

Category 2 (H319) Category 3 (H336)

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P240 - Ground and bond container and receiving equipment

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

2.3. Other hazards

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB)

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Component	CAS No	EC No	Weight %	CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and
-----------	--------	-------	----------	--

Revision Date 20-Oct-2023

				UK SI 2020/1567
Isopropyl alcohol	67-63-0	200-661-7	>95	Flam. Liq. 2 (H225)
				Eye Irrit. 2 (H319)
				STOT SE 3 (H336)

REACH registration number	01-2119457558-25

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Propan-2-ol

Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.				
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Get medical attention if symptoms occur.				
Ingestion	Do NOT induce vomiting. Get medical attention.				
Inhalation	Remove to fresh air. Get medical attention. If not breathing, give artificial respiration.				
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.				
4.2. Most important symptoms and	4.2. Most important symptoms and effects, both acute and delayed				
	Difficulty in breathing. May cause central nervous system depression: Inhalation of high				

Difficulty in breathing. May cause central nervous system depression: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

CO₂, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Do not use water jetstream. Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂), peroxides.

5.3. Advice for firefighters

Propan-2-ol

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges. Avoid contact with skin, eyes or clothing.

6.2. Environmental precautions

Should not be released into the environment. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Remove all sources of ignition. Soak up with inert absorbent material. Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. Keep in suitable, closed containers for disposal.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Keep away from open flames, hot surfaces and sources of ignition. Use spark-proof tools and explosion-proof equipment. Use only non-sparking tools. Take precautionary measures against static discharges. Do not get in eyes, on skin, or on clothing. Do not breathe mist/vapors/spray. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and flame. Flammables area. Keep container tightly closed in a dry and well-ventilated place.

Technical Rules for Hazardous Substances (TRGS) 510Class 3Storage Class (LGK) (Germany)Class 3

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

FSUP7490

Propan-2-ol

List source(s): **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE -** 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

Component	The United Kingdom	European Union	Ireland
Isopropyl alcohol	STEL: 500 ppm 15 min		TWA: 200 ppm 8 hr.
	STEL: 1250 mg/m ³ 15 min		STEL: 400 ppm 15 min
	TWA: 400 ppm 8 hr		Skin
	TWA: 999 mg/m ³ 8 hr		

Biological limit values

List source(s):

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL) See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Isopropyl alcohol 67-63-0(>95)				DNEL = 888mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Isopropyl alcohol 67-63-0 (>95)				DNEL = 500mg/m ³

Predicted No Effect Concentration (PNEC)

According to our experience and to the information provided to us, the product does not have any harmful effects if it is used and handled as specified. See values below.

Component	Fresh water	Fresh water sediment	Microorganisms in sewage treatment	,
	PNEC = 140.9mg/L	PNEC = 552mg/kg	PNEC = 2251 mg/L	PNEC = 28mg/kg
67-63-0 (>95)		sediment dw		soil dw

Component	Marine water	Marine water sediment	Marine water intermittent	Food chain	Air
Isopropyl alcohol	PNEC = 140.9mg/L	PNEC = 552mg/kg		PNEC = 160mg/kg	
67-63-0 (>95)		sediment dw		food	

8.2. Exposure controls

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation, especially in confined areas. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye ProtectionGoggles (European standard - EN 166)

Protective gloves

Hand Protection

Glove material
Butyl rubberBreakthrough timeGlove thicknessEU standardGlove commentsNitrile rubber> 480 minutes0.5 mmEN 374Permeation rate < 0.9 µg/cm2/min</td>Nitrile rubber> 360 - 480 minutes0.35 - 0.55 mmAs tested under EN374-3 Determination of
Resistance to Permeation by Chemicals

Propan-2-ol

ĺ	Viton (R)	> 480 minutes	0.4 mm	
	Neoprene	< 40 minutes	0.7 mm	

Skin and body protection Wear appropriate protective gloves and clothing to prevent skin exposure.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly
Large scale/emergency use	Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced Recommended Filter type: Organic gases and vapours filter Type A Brown conforming to EN14387
Small scale/Laboratory use	Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. Recommended half mask:- Valve filtering: EN405; Half mask: EN140; plus filter, EN 141 When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls No infor

ntrols No information available.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State	Liquid		
Appearance	Colorless		
Odor	Alcohol-like		
Odor Threshold	No data available		
Melting Point/Range	-89.5 °C / -129.1 °F		
Softening Point	No data available		
Boiling Point/Range	81 - 83 °C / 177.8 - 181.4 °F	@ 760 mmHg	
Flammability (liquid)	Highly flammable	On basis of test data	
Flammability (solid,gas)	Not applicable	Liquid	
Explosion Limits	Lower 2 Vol%		
	Upper 12 Vol%		
Flash Point	12 °C / 53.6 °F	Method - Abel Closed Cup (BS 2000 Part 170, IP 170, AS/NZS 2106)	
Autoignition Temperature	425 °C / 797 °F	ASTM E-659	
Decomposition Temperature	No data available		
рН	7	1% ag. sol	
Viscosity	2.27 mPa.s at 20 °C	•	
Water Solubility	Miscible		
Solubility in other solvents	No information available		
Partition Coefficient (n-octanol/water)			
Component	log Pow		
Isopropyl alcohol	0.05		
Vapor Pressure	43 mmHg @ 20 °C		
Density / Specific Gravity	0.785	ASTM D-4052	
Bulk Density	Not applicable	Liquid	
Vapor Density	2.1 @ 20 °C / 68 °F	(Air = 1.0)	

Propan-2-ol

Particle characteristics

Not applicable (liquid)

9.2. Other information

Molecular Formula Molecular Weight VOC Content(%) Explosive Properties

Evaporation Rate Thermal conductivity Refractive index Surface tension Coefficient of expansion Specific heat capacity Dielectric constant Heat of vapourisation C3 H8 O 60.1 100% (Organic Carbon (by mass) = 59.9 %) (EC/1999/13) Not explosive explosive air/vapour mixtures possible Vapors may form explosive mixtures with air 1.7 - ASTM D 3539 (Butyl acetate = 1.0) 0.137 W/m °C at 20 °C / 68 °F 1.377 at 20 °C / 68 °F (ASTM D-1218) 22.7 mN/m at 20 °C / 68 °F 0.0009 / °C 3 kJ/kg °C at 20 °C / 68 °F 18.6 at 20 °C / 68 °F

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity	None known, based on information available
10.2. Chemical stability	Stable under normal conditions.
10.3. Possibility of hazardous react	ions
Hazardous Polymerization Hazardous Reactions	Hazardous polymerization does not occur. None under normal processing.
10.4. Conditions to avoid	Heat, flames and sparks. Keep away from open flames, hot surfaces and sources of ignition.
10.5. Incompatible materials	Strong oxidizing agents. Acids. Halogens. Acid anhydrides.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO₂). peroxides.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral Dermal Inhalation Based on available data, the classification criteria are not met Based on available data, the classification criteria are not met Based on available data, the classification criteria are not met

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Isopropyl alcohol	5045 mg/kg (Rat) 3600 mg/kg (Mouse)	12800 mg/kg (Rat)	72.6 mg/L (Rat)4 h

Propan-2-ol		Revision Date	20-Oct-2023
(b) skin corrosion/irritation;	Based on available data, the classification criteria are not met		·····
(c) serious eye damage/irritation;	Category 2		
(d) respiratory or skin sensitization; Respiratory Skin	Based on available data, the classification criteria are not met Based on available data, the classification criteria are not met		
(e) germ cell mutagenicity;	Based on available data, the classification criteria are not met		
(f) carcinogenicity;	Based on available data, the classification criteria are not met There are no known carcinogenic chemicals in this product		
(g) reproductive toxicity;	Based on available data, the classification criteria are not met		
(h) STOT-single exposure;	Category 3		
Results / Target organs	Central nervous system (CNS).		
(i) STOT-repeated exposure;	Based on available data, the classification criteria are not met		
Target Organs	None known.		
(j) aspiration hazard;	Based on available data, the classification criteria are not met		
Symptoms / effects,both acute and delayed	May cause central nervous system depression. Inhalation of h cause symptoms like headache, dizziness, tiredness, nausea		ntrations may
11.2. Information on other hazards			

Endocrine Disrupting Properties	Assess endocrine disrupting properties for human health.	This product does not contain any
	known or suspected endocrine disruptors.	

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity Ecotoxicity effects

. Do not empty into drains.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Isopropyl alcohol	LC50: = 9640 mg/L, 96h flow-through (Pimephales promelas) LC50: > 1400000 µg/L, 96h (Lepomis macrochirus) LC50: = 11130 mg/L, 96h static (Pimephales promelas) LC50: = 10000000 µg/L, 96h (Daphnia)	13299 mg/L EC50 = 48 h 9714 mg/L EC50 = 24 h	EC50: > 1000 mg/L, 72h (Desmodesmus subspicatus) EC50: > 1000 mg/L, 96h (Desmodesmus subspicatus)

Component	Microtox	M-Factor
Isopropyl alcohol	= 35390 mg/L EC50 Photobacterium phosphoreum	
	5 min	

Propan-2-ol

12.2. Persistence and degradability Persistence	Expected to be biodegradable Persistence is unlikely, based on information available.	
12.3. Bioaccumulative potential	Bioaccumulation is unlikely	
Component	log Pow	Bioconcentration factor (BCF)
Isopropyl alcohol	0.05	No data available
<u>12.4. Mobility in soil</u>	The product contains volatile organic compour surfaces Will likely be mobile in the environme air	
Surface tension	22.7 mN/m at 20 °C / 68 °F	
<u>12.5. Results of PBT and vPvB</u> assessment	Substance is not considered persistent, bioacc and very bioaccumulative (vPvB).	cumulative and toxic (PBT) / very persistent
<u>12.6. Endocrine disrupting</u> properties Endocrine Disruptor Information	This product does not contain any known or su	uspected endocrine disruptors
<u>12.7. Other adverse effects</u> Persistent Organic Pollutant Ozone Depletion Potential	This product does not contain any known or su This product does not contain any known or su	

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products	Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.
Contaminated Packaging	Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.
European Waste Catalogue (EWC)	According to the European Waste Catalog, Waste Codes are not product specific, but application specific.
Other Information	Waste codes should be assigned by the user based on the application for which the product was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with local regulations.

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

<u>14.1. UN number</u>	UN1219
14.2. UN proper shipping name	Isopropanol (Isopropyl alcohol)
14.3. Transport hazard class(es)	3
14.4. Packing group	II

<u>ADR</u>

<u>14.1. UN number</u> <u>14.2. UN proper shipping name</u> <u>14.3. Transport hazard class(es)</u> <u>14.4. Packing group</u>	UN1219 Isopropanol (Isopropyl alcohol) 3 II
IATA	
<u>14.1. UN number</u> <u>14.2. UN proper shipping name</u> <u>14.3. Transport hazard class(es)</u> 14.4. Packing group	UN1219 Isopropanol 3 II
14.5. Environmental hazards	No hazards identified
14.6. Special precautions for user	No special precautions required.
14.7. Maritime transport in bulk according to IMO instruments	Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Isopropyl alcohol	67-63-0	200-661-7	-	-	Х	Х	KE-29363	Х	Х

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Isopropyl alcohol	67-63-0	Х	ACTIVE	Х	-	Х	Х	Х

Legend: X - Listed '-' - Not Listed KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization		REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Isopropyl alcohol	67-63-0	-	Use restricted. See item 75. (see link for restriction details)	-

REACH links

https://echa.europa.eu/substances-restricted-under-reach

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) -	Seveso III Directive (2012/18/EC) -

Propan-2-ol

		Qualifying Quantities for Major Accident Notification	Qualifying Quantities for Safety Report Requirements
Isopropyl alcohol	67-63-0	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

See table for values

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Isopropyl alcohol	WGK1	

Component	France - INRS (Tables of occupational diseases)
Isopropyl alcohol	Tableaux des maladies professionnelles (TMP) - RG 84

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
lsopropyl alcohol 67-63-0 (>95)		Group I	

15.2. Chemical safety assessment

A Chemical Safety Assessment/Report (CSA/CSR) has been conducted by the manufacturer/importer

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H225 - Highly flammable liquid and vapor

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

Legend

CAS - Chemical Abstracts Service	TSCA - United States Toxic Substances Control Act Section 8(b)
	Inventory
EINECS/ELINCS - European Inventory of Existing Commercial Chemical	DSL/NDSL - Canadian Domestic Substances List/Non-Domestic
Substances/EU List of Notified Chemical Substances	Substances List
PICCS - Philippines Inventory of Chemicals and Chemical Substances	ENCS - Japanese Existing and New Chemical Substances
IECSC - Chinese Inventory of Existing Chemical Substances	AICS - Australian Inventory of Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances	NZIOC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit ACGIH - American Conference of Governmental Industrial Hygienists DNEL - Derived No Effect Level RPE - Respiratory Protective Equipment LC50 - Lethal Concentration 50% NOEC - No Observed Effect Concentration PBT - Persistent, Bioaccumulative, Toxic	 TWA - Time Weighted Average IARC - International Agency for Research on Cancer Predicted No Effect Concentration (PNEC) LD50 - Lethal Dose 50% EC50 - Effective Concentration 50% POW - Partition coefficient Octanol:Water vPvB - very Persistent, very Bioaccumulative
ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code OECD - Organisation for Economic Co-operation and Development BCF - Bioconcentration factor Key literature references and sources for data https://echa.europa.eu/information-on-chemicals Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, F	ICAO/IATA - International Civil Aviation Organization/International Air Transport Association MARPOL - International Convention for the Prevention of Pollution from Ships ATE - Acute Toxicity Estimate VOC - (Volatile Organic Compound)

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Creation Date	01-Sep-2009
Revision Date	20-Oct-2023
Revision Summary	Not applicable.

This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet